

GE Healthcare



OEC Elite™ MiniView™ C-arm

Digital Mobile C-arm
Technical Data

Changing the Mini C-arm Experience



510(k) pending at FDA. Not available for sale in the United States.
Cannot be placed on the market or put into service until it has been
made to comply with the Medical Device Directive requirements for
CE marking.

Specifications

X-ray System

- X-Ray Tube
 - Compact Monoblock
- Focal Spot
 - .033 mm
- Generator
 - 12.8 W
- kVP range
 - 40 - 80 kVp
- mA range
 - 0.02 - 0.16 mA
- Maximum Output
 - 0.16 mA 80 kVp
- Dose Rate Calculation
 - AKR/DAP

Imaging System

- Detector
 - CMOS flat detector
- FOV Size
 - 4" (10 cm) Mag
 - 5" (13cm) Normal
- Detector Size (resolution)
 - 1.3 k x 1.3 k pixels
- Pixel Size (spacing)
 - 100 microns
- DQE
 - (0) - 70%

Viewing System

- Monitors
 - Dual medical 19" (48 cm)
 - Monochromatic LCD
 - Anti-glare panels
- Monitor Resolution
 - 1280 x 1024 pixels
- Displayed image: primary live image
 - 11.4" (29 cm) diameter
- Displayed image: reference image
 - 11.4" (29 cm) diameter
- Image Size
 - 1.3 k x 1.3 k 16 bit image processing
 - 1 k x 1 k displayed image
- Tilt Motion
 - 10° up / 10° down
- Swing + Swivel Rotation Motion
 - 180° + 270°
- Viewing Angle
 - 170° horizontal & vertical
- Max Panel Brightness
 - 1400 Cd/m²
- Max Contrast Ratio
 - 1000:1
- Touch Screen
 - Right monitor

Surgeon Tube Head Controls

- X-ray exposure button
- Dual tube head control panels
 - Auto Technique
 - Low Dose Mode (max .08 mA - 80 kVp)
 - Manual kV/mA adjustment
 - Save
 - Swap
 - Print
 - Laser Aimer
 - Magnification
 - Image rotate
 - Auto Brightness/Contrast
 - Manual Brightness/Contrast adjustments
 - Alarm Reset
 - Smart Lock Button

Imaging Features

- Annotation/Measurements
- Smart Metal
 - Detects metal in the field and optimizes image quality
- AutoTrak
 - Automatically seeks anatomy anywhere in the field and selects optimal technique
- Zoom-Room
- Auto X-Ray Technique Control
- Edge Enhancement
- Last Image Hold
- Auto-save/Auto swap
 - Configurable
- Noise Reduction
- Motion Artifact Reduction
- Flip/Invert
- Negate

C-arm Physical Specifications

- Balanced Pivot C /Fork
 - Carbon fiber Composite material
- SmartLock Button
 - Anti Drift Locking Mechanism
 - Single button locks 4 joints
 - Electro-mechanical
- SID
 - 17.6" (45cm)
- Free Space
 - 13.4" (34 cm)
- C-arm Depth
 - 18" (46 cm)
- Frictionless Orbital Rotational Sleeve
 - 120° (90° Underscan, 30° Over Scan)
- C-arm Horizontal Travel
 - 77.2" (196 cm)

- Counterbalanced C-arm Vertical Travel
 - 33.4" (85cm)
- C-arm Panning Motion
 - 366°
- C-arm Lateral Rotation
 - 380° (+/- 190°)
- Weight
 - 220 kg (485 lbs)
- Foot Print
 - 0.64 m²
- Size
 - 70.5" x 29.0" x 38.3" (179 x 74 x 97 cm)
- C-arm Motion
 - 5 joints: Orbital, Lateral, Upper and Lower Horizontal, Vertical
- Footswitch
 - Wired
 - Configurable dual pedal
 - Save, Print, Save & Print
- Skin Spacer mount

Electrical

- Backup Battery
- Input Power (60/50 Hz)
 - 100/110/115/120/127VAC @ 4.5A
 - 200/220/230/240VAC @ 2.3A
- Auto Power Sensing

Data Management & Connectivity


- Water Resistant Keyboard
- Removable Storage
 - USB
- Hard Drive Storage
 - 100,000 images
- Printer
 - optional
- DICOM (3.0)
 - MPPS
 - RDSR - Radiation Dose Structured Report
 - Query and Retrieve
 - Modality Worklist
 - Print
 - Storage
 - Storage Commitment
- Wireless DICOM
 - optional
- Wireless Frequency
 - 2.4G, 5G

Regulatory Compliance

- IEC60601-1
- U.S. 21 CFR Subchapter J

Dimensions

510(k) pending at FDA. Not available for sale in the United States. Cannot be placed on the market or put into service until it has been made to comply with the Medical Device Directive requirements for CE marking.



©2016 General Electric Company – All rights reserved.

General Electric Company reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your GE Representative for the most current information.

*GE, GE Monogram, OEC Elite and MiniView are trademarks of General Electric Company.

GE OEC Medical Systems, Inc., doing business as GE Healthcare.

510(k) pending at FDA. Not available for sale in the United States. Cannot be placed on the market or put into service until it has been made to comply with the Medical Device Directive requirements for CE marking.

Healthcare Re-imagined

GE is dedicated to helping you transform healthcare delivery by driving critical breakthroughs in biology and technology. Our expertise in medical imaging and information technologies, medical diagnostics, patient monitoring systems, drug discovery, and biopharmaceutical manufacturing technologies is enabling healthcare professionals around the world discover new ways to predict, diagnose and treat disease earlier. We call this model of care “Early Health.” The goal: to help clinicians detect disease earlier, access more information and intervene earlier with more targeted treatments, so they can help their patients live their lives to the fullest. Re-think, Re-discover, Re-invent, Re-imagine.

USA

GE OEC Medical Systems, Inc.
384 Wright Brothers Drive
Salt Lake City, UT 84116
Tel: +1 801-328-9300
Fax: +1 801-328-4300

Japan

GE Healthcare Asia Pacific
4-7-127, Asahigaka
Hino-shi, Tokyo
191-8503 Japan
Tel: +81 42 585 5111

ANZ

Building 4B, 21 South St
Rydalme NSW 2116
Australia
Tel: +1 300 722 229 (Australia)
+0 800 434 274 (New Zealand)

ASEAN

1 Maritime Square #31-01
HarbourFront Centre
Singapore 099253
Tel: +65 6291 8528

Korea

GE Tower 71-3
Cheongdam-dong
Kangnam-gu, Seoul
Korea 135-100
Tel: +82 2 6201 3114

Authorized EU Representative

GE Medical Systems, SCS
283 rue de la Miniere
78533 Buc
France
Tel: +33 1 30 70 94 35

www.gehealthcare.com



imagination at work